

## MSM 600 Die Spraying Machine



**manufacturer :**  
partnership

**Product number:**  
MS5060

## Description

| Die Spraying Machine       | for die casting machines      |
|----------------------------|-------------------------------|
| <b>Model</b>               | MSM 600                       |
| <b>Drive</b>               | AC Servo motor                |
| <b>Axis</b>                | 1 vertical axis               |
| <b>Stroke</b>              | 600mm                         |
| <b>Spray system</b>        | 1 spray circuit for lubricant |
|                            | 1 blow circuit                |
|                            | 1 high pressure blow circuit  |
| <b>Driving speed, max.</b> | 2,1 m/s                       |

|                                         |                                     |
|-----------------------------------------|-------------------------------------|
| <b>Control system</b>                   | MC1 Micro Control                   |
| <b>Scale of delivery</b>                | including 5m connecting cable       |
|                                         | connector for die casting machine   |
|                                         | manual                              |
| <b>Adapted for die casting machines</b> | from 1000kN to 1600kN locking force |

|                                                                                                                                                                                                                  |            |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|
| <b>Description</b>                                                                                                                                                                                               |            |
| The MSM spraying machine contributes an essential part in order to ensure constant production conditions for hot and cold chamber die casting machines.                                                          |            |
| <b>Advantages:</b>                                                                                                                                                                                               |            |
| <ul style="list-style-type: none"> <li>• Robust, die casting suitable construction</li> <li>• Highest die casting quality due to optimal formation of a release agent film</li> <li>• Made in Germany</li> </ul> |            |
| Delivery time                                                                                                                                                                                                    | on request |
| Price                                                                                                                                                                                                            | on request |

