

Aluminium remelting plant IA2541, used



manufacturer :
Sonstige

Product number:
IA2541

Description

Aluminium remelting plant

Input materials	Aluminium scrap, schredder scraps, lacquered
Capacity	Approx. 120 t/Tag
Final product	8 - 12 kg ingots
Comments	

Charging machine

Manufacturer	GHI - GUINEA HERMANOS INGENIEROS
--------------	----------------------------------

Charging machine	
Type	vibration chute moveable by rails, liftable by hydraulic scissor
Year of Manufacture	2008
Capacity chute	7500 kg
Lifting height	3500 mm
Table size	80 A, 400 V, 3-Phasen, 50 Hz

Aluminium remelting plant	
Input materials	Aluminium scrap, schredder scraps, lacquered
Capacity	Approx. 120 t/Tag
Final product	ingots 8 - 12 kg
Comments	

Melting Furnaces	
Manufacturer	GHI - GUINEA HERMANOS INGENIEROS
Type	Shaft furnace TFA 5, fixed
Year of Manufacture	2008
Capacity chute	25 t
Melting rate	5 ton/h
Heating	Propan
Burner	North American
Type	With flame detecor
Burner capacity	2.800.000 kcal
Number	4
Input material	Aluminium scrap, Schredder scraps, lacquered
Burner fan	30 kW

Melting Furnaces

Max. temperature in furnace room	1100 °C
Dimensions (LxBxH)	5000 x 6200 x 7200
Electrical connection	30 KW, (60 A), Burner fan 22 kW (44 A) hydraulic group (total with furnace TFA-5 und RAN-R-25-B), 400 V, 3Ph, 50 Hz.

Melting furnace with metal pump LOTUS and vertical vibrations conveyor for swarfs

Manufacturer	TECHNI-THERM
Type	Heard furnace, hydraulically tiltable
Year of Manufacture	2010
Furnace dimensions	24 t
Outside	
Width	6700 mm
Length	4700 mm
Inside	
Width	3600 mm
Length	3500 mm
Furnace height	4400 mm
Bath height	800/900 mm
Furnace door	3000 x 632 mm
Installed power	2500 kW
Heating	Propan gas, max. 290 Nm³/h, Oxygen
Input materials	Scrap and swarfs
Furnace door dimension (L x H)	4700 x 1200 mm
Charging opening top	900 800 mm

Melting furnace with metal pump LOTUS and vertical vibrations conveyor for swarfs

Metal pumps

LOTUS, Type TT 35 SO, 11 kW

Holding/casting furnaces

Manufacturer GHI – GUINEA HERMANOS INGENIEROS

Type Hydraulisch kippbarer Herdofen

Year of Manufacture 2008

Capacity 25 t

Furnace bath

Width

Bath height 950 mm

Bath length 3400 mm

Furnace outer dimensions

Width 8600 mm

Length 6500 mm

Height 7800 mm

Installed power 2.500.000 kcal/h

Heating 2500 kW

Heating

Type North-American Mfg. Co Allumage

Burner power

Number 2

Burner air fan 18,5 kW, 3000 U/min

Input material Liquid metal

Furnace door dimension (L x H) 4700 x 1200 mm

Ingot casting line

Manufacturer	System Fuss
Type	Casting wheel
Year of Manufacture	2008
Ingot weight	8 - 12 kg
Casting rate / h	ca. 5 t/h
Heating moulds	Burner
Type of cooling moulds	Water / air
Atotomatic ingot stacking machine	yes
Line dimensions	
Length casting belt	19425 mm
Cooling line	10080 mm
Total length with stacking	42070 mm
Cooling water	Cooling tower, internal circulation

Waste gas filter plant

Manufacturer	SEMECA
Year	2008
Waste gas amount melting furnaces 1 + 2	60.000 Nm³/h
Waste gas amount after after-burner	15.000 m³/h
Waste gas amount furnace hoods	10 a´ 15.000 m³/h
Waste gas amount holding furnaces	5 a´ 8.000 m³/h
Waste gas amount Furnace hoods	20 a´ 25.000 m³/h
Total Waste gas amount	115 a´ 120.000 m³/h
Capacity data	
Total dust	

Waste gas filter plant

Law 40 mg/Nm³

Gurantee SEMECA < 20 mg/Nm³

Dioxin

Law 0,1 ng/Nm³

Gurantee SEMECA 0.1 ng/Nm³

HCl

Law 50 mg/Nm³

Gurantee SEMECA < 50 mg/Nm³

Delivery time immediately

Price on request





